



LUFT3

Lung Ventilator for ICU
Neonatal, Pediatric & Adult



Our commitment to life

Leistung is more than a manufacturer of lung ventilators for ICU and Emergency. Leistung's lung ventilators, besides being products of technological excellence and performance, they also carry the values of all the professionals involved in the process, from its conception to its commercialization, who are aware about the importance of a life-supporting device.

Therefore, we are proud to say that, while we are an industry, our essence lies in the trust that professionals and patients place in us. It is our commitment to life that makes us go further!



www.leistungbrasil.com

+55 47 3371 2741

LUFT3

TECNOLOGY allied
to QUALITY OF LIFE.





LUFT3

Lung Ventilator for ICU

Adult | Pediatric | Neonatal

The lung ventilator for Intense Care Units (ICU) LUFT3, counts with integrated 17" touch screen technology and offers a complete range of ventilation modes which allows the monitoring of the patient's condition.

VENTILATION MODES

ADULT/PEDIATRIC

- VCV assisted/controlled
- PCV assisted/controlled
- PSV/CPAP
- PRVC assisted/controlled
- SIMV (VCV) + PSV
- SIMV (PCV) + PSV
- MMV + PSV
- PSV + assured VT
- Biphasic pressure (APRV + PSV)
- NIV
- HFNC

NEONATAL


- VCV assisted/controlled
- PCV assisted/controlled
- PSV/CPAP
- SIMV (PCV) + PSV
- Continuous flow assisted/controlled
- Nasal CPAP
- HFNC

FUNCTIONALITY AND PERFORMANCE



STRESS INDEX

The stress index is performed with minimal interference in the ventilatory cycle and results in a numerical value of easy interpretation, promoting a practical, safe and effective analysis of the patient ventilation. It is a measure of respiratory the stress caused in the alveoli either by collapse or hyperdistension.



PRVC

It combines the best of conventional controlled ventilation modes of volume and pressure, providing the volume adjusted by the operator with as little pressure as possible.

The function uses free flow waveform formation, control with feedback of the compliance and resistance of the patient.



LUFT3
Lung Ventilator for ICU

SPECIAL FEATURES

- 100 % oxygen up to 20 min. with automatic alarm silence;
- Adaptation of the patient's interface or change of the circuit with recalibration without having to turn off the equipment and keeping track of the patient's log;
- Automatic theoretical weight calculation and interface selection according to the patient;
- Altitude compensation;
- Configuration of the monitored variables;
- Flow curve 50 % descending;
- Intuitive Interface;
- Gas measurement with BTPS correction;
- Smart ventilator, records the user preference after 10 uses.
- LCD Screen tilt angle adjustment
- Log for 1000 alarms and events with date and time



Adjustment of the
ALARM
VOLUME



6 HOURS
battery life



Intuitive Interface
with Adjustment
of the **MONITORED**
VARIABLES



Timed **NEBULIZER**
with Inspiration
flow and FiO₂
compensation

GRAPHICAL INTERFACE



INITIAL SCREEN SETUP

- Patient selection
- Gender
- Height
- Weight
- Automatic theoretical weight calculation
- Ventilation level per mL/kg
- Type of artificial airway
- Type of humidification
- Line test
- Circuit compliance measurement
- Last patient function

LUFT3

Lung Ventilator for ICU

OPERATIONAL VISUALIZATION

- Graphical pressure bar
- Indicator of spontaneous/controlled cycles
- Battery charge level
- Programation of the ventilatory variables

ADULT AND PEDIATRIC

Customizable selection
of up to

5

SIMULTANEOUS GRAPHICS

- Pressure/Time
- Flow/Time
- Volume/Time
- Volume/Pressure
- Flow/Volume
- Pressure/Flow

NEONATAL

Customizable selection
of up to

3

SIMULTANEOUS GRAPHICS

- Pressure/Time
- Flow/Time
- Volume/Time

LUFT3

Lung Ventilator for ICU

LUNG MECHANICS

- AutoPEEP
- Slow vital capacity
- Dynamic compliance
- Static compliance
- PV curve with low flow
- Elastance
- Stress Index
- Tobin Index
- P0.1 - Airway obstruction pressure
- Expiratory resistance
- Inspiratory resistance
- Work of breathing
- Esophagus pressure (optional)



LUFT3

Lung Ventilator for ICU

PARAMETERS**CONTROLS**

FiO ₂	21 to 100 %
Inspiratory time	0.1 to 30 s
I:E Ratio	5:1 - 1:99
Ventilator Frequency	1 - 180 r.p.m.
Tidal Volume	2.0 to 2500 mL, up to 4000 ml in pressure modes
Minute Volume	0.01 to 25.0 L
Sensibility	By Flow: 0.1 to 15 L/min. By Pressure: -0.1 to -15.0 cmH ₂ O (PEEP compensated)
Controlled Pressure (PCV)	1 to 95 cmH ₂ O (over PEEP)
Support Pressure (PSV)	0 to 80 cmH ₂ O (over PEEP)
Inspiratory Pressure	-10 to 120 cmH ₂ O
Rise Time	6 levels
Expiratory Sensibility	5 to 80 %
Apnea Time	5 to 60 s
PEEP/CPAP	0 to 50 cmH ₂ O
Nebulization	1 to 20 min. synchronized with automatic compensation of the inspired volume and FiO ₂
Inspiratory Flow	0 to 200 L/min.
Base Flow	Off up to 50 L/min.
Expiratory Flow	Up to 200 L/min.
Automatic Inspiratory Pause (VCV mode):	0.1 - 2.0 s with plateau pressure value
Manual Inspiratory and Expiratory Pause	Up to 30 s
O ₂ 100%	1 to 20 min.
Flow Waveform	Square/Descending 100 %/Descending 50 %/Sinusoidal/Ascending
Inspiratory Pressure Inner Safety Valve	Adjusted in 120 cmH ₂ O
Pressure Regulating Valve for Air and O ₂ Input	Built into the equipment
RS232 Signal Connector	For external communication with the software and signals input
USB Signal Connector	For equipment's service and software update
TGI	Synchronized with the exhalation phase
Sigh (VCV mode)	Cycles per hour, quantity, maximum tidal volume
Automatics Scales	Automatic for amplitude and adjustable per time
Graphics Freeze	With grid for easy interpretation of the values
Standby	Keep the ventilator in standby mode without changing the setup
Backup Ventilation	Available in all ventilatory modes
Altitude Compensation	0 to 6000 masl
Alarm Sound Level	20 to 100 %

PARAMETERS**MONITORIZATION**

Airway Pressure: Peak	0 to 120 cmH ₂ O
Airway Pressure: Plateau	0 to 120 cmH ₂ O
Airway Pressure: Mean	0 to 120 cmH ₂ O
Airway Pressure: Base (PEEP)	0 to 50 cmH ₂ O
Inspiratory Time	0 to 30 s
Expiratory Time	0 to 30 s
I:E Ratio	49:1 to 1:99
Inspiratory Pause	0 to 30 s
Inspired/Expired Tidal Volume (Distal and Proximal)	0 to 5.0 L
Peak Inspiratory Flow (Distal and Proximal)	999 L/min.
Peak Expiratory Flow (Distal and Proximal)	999 L/min.
Dynamic Compliance	999 mL/cmH ₂ O
Total and Spontaneous Frequency	250 r.p.m.
Graphical Indicator of Spontaneous and Mechanical Cycles	Symbols and graphs
Minute Volume (Distal and Proximal) total and spontaneous	0 to 25 L/min.
FiO ₂ Concentration	21 to 100%
Constant of inspiratory and expiratory time	9.99 s
Compressible Volume	399 mL
Ti/Ttot Ratio	0.98
Total Leakage	50 L/min.
Ventilation Level (mL/kg)	99.0 mL/kg
Battery Charge Level	0 to 100%
Patient Circuit's Compliance	4.0 mL/cmH ₂ O

GENERAL

SPECIAL CHARACTERISTICS

Current time and date
Time and date when the equipment was turned on
Touch screen function lock
Graphical indicator of external power supply and battery
Proportional indicator of battery charge level
Indicator bar of the parameters adjustment range
Graphical bar of the ventilatory pressure with indicator of the alarms level
FiO₂ reading through Galvanic Cell or Pneumotachograph
Standby symbol
Alarms log symbol
Automatic compensation of the breathing circuit's compliance
Internal, permanent and non-consumable sensor

PROGRAMMABLE ALARMS

Maximum pressure
Minimum pressure
Maximum tidal volume
Minimum tidal volume
Maximum minute volume
Minimum minute volume
Maximum frequency
Minimum frequency
FiO₂
PEEP
Apnea

COMPLEMENTARY MESSAGES

Without exhalation sensor
Without proximal sensor
Active oxygen cell
Estimated patient weight

AUTOMATIC ALARMS

Power failure
Interrupted cycle
Air/O₂ input pressure (low and high)
Low Battery (inoperative battery)
Microprocessor (inoperative ventilator)
Inverted I:E Ratio
Patient disconnection
Proximal sensor disconnection

LUFT3

Lung Ventilator for ICU

PARAMETERS

GRAPHICAL TENDENCIES

Tidal Volume
Minute Volume
Frequency
Dynamic Compliance
Peak Pressure
Base Pressure
Flow
Airway resistance
Graphical tendencies up to 72 hours with the aid of grids for analysis

NUMERICAL TENDENCIES

AutoPEEP
Dynamic compliance
Static compliance
Inspiratory resistance
Expiratory resistance
Stress Index

INTERNAL POWER SUPPLY

Nominal voltage	10.8 V ~ 11.1 V
Nominal capacity	13.2 Ah
Type	Lithium Battery (Li+)
Battery	360 min. autonomy

GENERALITIES

Medical Product Classification	Class III
Operation Mode	Continuous Operation
Classification Against Electric Shock (Isolation)	Class I - Internally Energized Equipment
Classification of Protection Against Electric Shock	Type B
Protection Level Against Nocive Penetration of Water	IP22

PNEUMATIC INPUT

Oxygen	DISS 9/16" – 18 Input
Air	DISS 3/4" – 16 Input
Pressure	250 – 700 kPa (2.5 - 7 bar)
Maximum Flow Consumption	Up to 180 L/min.

PHYSICAL CHARACTERISTICS

Height	1473 mm
Width	550 mm
Depth	530 mm
Equipment's Weight	28.0 kg
Case's Weight	10.0 kg
Monitor's Weight	5.4 kg
Trolley's Weight	12.6 kg
Touch Screen	17 inches
LCD LED Monitor	With angulation adjustment
Trolley	Anticorrosive plastic material
Castors	4, being 2 with brakes

POWER SUPPLY

Voltage - Current	100 V – 240 V ~ 0.6 A – 0.29 A
Frequency	47 to 63 Hz
Commutation to Battery	Voltages Lower than 90 Vac.




LEISTUNG

**Leistung Equipamentos Ltda.**

202, João Ropelatto St.

Nereu Ramos - 89265-520

Jaraguá do Sul - SC - Brazil

Phone: +55 47 3371 2741 **+55 47 99985 2793****E-mail: leistung@leistungbrasil.com****Site: www.leistungbrasil.com****Technical Support****+55 47 99985-6173** 

ANVISA Register No.: 80203470012

Op. Auth. ANVISA: GHL3983MX9H2

Certification EN ISO 13485:2016

Certification GMP ANVISA RDC 16

Certification 199844-2016-CE-BRA-NA-PS

